

Roller **LYNX** Garage Door



- ▶ Space Saving Design
- ▶ Robust Construction
- ▶ Faultless Operation
- ▶ Inherent Security

POWERED BY

Eurodrive

5 YEAR WARRANTY

SEE TERMS & CONDITIONS

ROLLING OUT

ACROSS THE UK



We know garage doors - inside and out!


ALLIANCE
DOOR ENGINEERING LTD


PROFILE
DOOR ENGINEERING
A trading style of Alliance Door Engineering Ltd



A trading style of Alliance Door Engineering Ltd



ALLIANCE DOOR ENGINEERING LTD

Roller **LYNX**

Garage Door



Contact us

Tel: 01942 683601 Tel: 0161 483 9611
 Fax: 01942 683607 Fax: 0161 483 9572
 www.alliancedoors.co.uk www.profiledoors.co.uk
 info@alliancedoors.co.uk info@profiledoors.co.uk

Manufacturer of consistently high quality doors & shutters



for over 10 years.

**Outstanding design
and exceptional value
giving you a totally coherent,
high quality result at a price you can really work with.**



Our space saving design is ideal for short driveways and on-street access.

The photocell beam will auto reverse the door when obstructed.

Heavy duty materials and mechanisms make for year-in, year-out security.

Enhanced thermal and acoustic insulation is ideal for internal garages - reduce noise, save on heating and help the environment.



Expertly crafted from high quality parts and finished in any colour from our extensive range, a garage door can be the finishing touch of style to any home.

SPECIFICATIONS

CURTAIN	77mm x 20mm heavy duty extruded aluminium lath, alternate laths double pop riveted, using high density glass fibre nylon endlocks, to prevent lateral movement. A high quality aluminium (78mm x 19mm) bottom rail incorporating a rubber weather seal is added to the base of the curtain for strength, rigidity and security.
MOTOR	Integral tubular motor fitted within electric resistance welded circular tube.
POWER	Single Phase (240V).
WEIGHT	20 KG per m2 applies to whole of door assembly.
BARREL TUBE	Lost bobbin system fitted to the "dummy end". Manual override facility on motor end (via eyelet). Safety brake fitted to non-motor end of barrel assembly. Crank handle supplied with each project.
FLAGS	Heavy duty aluminium endplates, 250/300mm square (depending upon height of shutter), with 45° section to back. High quality aluminium guides are extruded from 95mm x 34mm section.
HOOD	Weatherproof hood made from 20swg galvanised/anodised material. This covers barrel mechanism & curtain from the elements when fixed externally.
FINISH	Standard stock colours are supplied with colour coordinated guides, endplates and canopy as standard. Alternative colours are available at an additional cost.
ACTIVATION	Remote control complete with 2No. transmitters.
AUTO-LOCK	Fitted with a patented auto-locking facility.
SAFETY	Retro-reflective photocell beam.
LIGHT	Courtesy light fitted as optional extra.

Alliance Door Engineering Ltd
 Unit D2(2) Moss Ind.Est.
 St Helens Rd Leigh WN7 3PT

Alliance Door Engineering Ltd maintain a policy of progressive design and reserve the right to modify the specifications without notice.